

OpenSees: Output/Recorders


Frank McKenna

2003 Users Workshop
Berkeley, CA
August 21-22, 2003

Sponsored by the National Science Foundation
through the Pacific Earthquake Engineering Research Center



Main Abstractions in OpenSees



Focus of this presentation

print:

To print information from the Domain at any time t

```
print <$fileName>
```

To print just nodal information

```
print <$fileName> -node <$node1 $node2 ...>
```

To print just element information

```
print <$fileName> -ele <-flag $flag> <$ele1 $ele2 ...>
```

logging:

To echo what is being printed on the screen to a file

```
logFile $fileName
```

node recorder:

To monitor what's happening at the nodes during the analysis

```
recorder Node <-file $fileName> <-time> <-node ($node1 $node2  
...)> <-nodeRange $startNode $endNode> <-node all> -dof ($dof1  
$dof2 ...) $respType
```

*valid respType are: **disp**, **vel**, or **accel**

If you want to see max, min & absolute max values

```
recorder EnvelopeNode ...
```

Or the drift between 2 nodes

```
recorder Drift $fileName <-time> $node1 $node2 $dof $perpDirn
```

element recorder:

To monitor what's happening at the elements, sections or materials during the analysis

```
recorder Element <-file $fileName> <-time> <-ele ($ele1 $ele2 ...)> <-eleRange $startEle $endEle> <-ele all> ($arg1 $arg2 ...)
```

***valid \$arg depend on the element**

Common to all beam-column elements: nonlinearBeamColumn, dispBeamColumn, beamWithHinges elements:

- globalForce – element resisting force in global coordinates (does not include inertial forces)
- localForce – element resisting force in local coordinates (does not include inertial forces)
- section \$secNum – to request response quantities from a specific section along the element length, where secNum is between 1 and the number of sections

If you want to see max, min & absolute max values

```
recorder EnvelopeElement ...
```

plot recorder:

To monitor what's being recorder in a file by a recorder!

```
recorder plot $fileName $windowTitle $xLoc $yLoc $xPixels $yPixels -columns $xCol0 $yCol0 <-columns $xCol1 $yCol1> <-columns $xCol2 $yCol2> ...
```

database:

To save the state of the model at time t for restarts

```
database databaseType $databaseName
```

This now adds commands to save & restore to a database:

```
save $commitTag
```

```
restore $commitTag
```